

Corning® HI 1060 Specialty Fiber

Single-mode Component Fiber

for High Performance Photonic Applications



Photonic
Materials

PI1263

Issued: August 2003

Supersedes: March 2003

Manufactured with Corning's patented outside vapor deposition process, Corning HI 1060 Specialty Fiber offers world-class durability and reliability. When used as component pigtails, this fiber allows for efficient fiber coupling within photonic products.

Applications

- Photonic products and fused fiber couplers
- Component fiber for EDFAs, couplers, other DWDM components
- Laser diode pigtails

Features

- Patented outside vapor deposition process provides outstanding consistency and uniformity
- Dual acrylate coating system provides excellent protection from microbend-induced attenuation
- Excellent geometry control
- High core index of refraction
- Efficient coupling
- High numerical aperture

Key Optical Specifications

Maximum Attenuation	2.1 dB/km @ 980 nm 1.5 dB/km @ 1060 nm
Cutoff Wavelength	920 nm $\pm$ 50 nm
Mode-field Diameter	5.9 μ m $\pm$ 0.3 μ m @ 980 nm 6.2 μ m $\pm$ 0.3 μ m @ 1060 nm

Key Geometric Specifications

Cladding Outside Diameter	125 μ m $\pm$ 0.5 μ m
Coating Outside Diameter	245 μ m $\pm$ 10 μ m
Core-to-cladding Offset	$\leq$ 0.3 μ m

Performance Characterizations

Operating Temperature	-60°C to 85°C
Nominal Delta	0.45%
Numerical Aperture (Typical)	0.14
Standard Lengths	0.5, 1, 2, 5 km
Proof Test	100, 200 kpsi

For More Information

For more information about Corning's leadership in specialty fiber technology, visit our website at www.corning.com/photonicmaterials.

To obtain additional technical information or an engineering sample, or to place an order for this product, please contact us:

Phone: +1-607-974-9974

Fax: +1-607-974-4122

E-mail: specialtyfiber@corning.com